



trd\_UI\tagsTable.pnl

tag	config name	revision	all SM	SM00	SM01	SM07	SM08	SM09	SM17
376	p_csmtrk_15tb	r2216							
377	p_zs_csmtrk_15tb	r2216							
380	p	r2216							
390	p	r2266							
396	p_csmtrk_15tb	r2266							
397	p_zs_csmtrk_15tb	r2266							
401	testpattern1	2008.1							
402	testpattern2	2008.1							
410	testpattern1	r2216							
411	testpattern2	r2216							
1000	cf_p_nozs_tb15_csmtrk_ptrg	r2272							
1001	cf_p_nozs_tb21_csmtrk_ptrg	r2272							
1002	cf_p_nozs_tb24_csmtrk_ptrg	r2272							
1003	cf_p_nozs_tb27_csmtrk_ptrg	r2272							
1004	cf_p_nozs_tb30_csmtrk_ptrg	r2272							
1201	cf_p_zs-s16c100_tb30_csmtrk_ptrg	r2311							
1202	cf_p_zs-s16c100-deh_tb30_csmtrk_ptrg	r2332							
1203	cf_p_zs-s16c100_tb30_csmtrk_ptrg	r2281							
1300	cf_p_zs-s16c40mn_tb30_csmtrk_ptrg	r2336							
1301	cf_p_nozs_tb30_csmtrk_ptrg	r2336							
1302	cf_p_zs-s16c100mn-deh_tb30_csmtrk_ptrg	r2336							
1400	p_autotrg	r2281							

load configuration

PHYSICS

DEFAULT ZS

DEFAULT NZS

store configuration

PHYSICS

DEFAULT ZS

DEFAULT NZS

CLOSE

click to show configuration for run type

select configuration, then press button to store

click to open panel

SELECT FED  
CONFIGURATION TAG

FED MESSAGE

BROWSER

SOR/EOR

SCRIPTS

HV RAMP DOWN:

- 400 V

HV RAMP UP:

+ 400 V